



HIGH MOBILITY BASE OR ROVER GNSS RECEIVER FOR SITE MEASUREMENT AND STAKEOUT APPLICATIONS

INTEGRATED GNSS RECEIVER, GNSS ANTENNA, RADIO AND BATTERY IN A SMALL LIGHTWEIGHT AND ROBUST HOUSING

RAPID DAILY BASE STATION SETUP WITH A SINGLE BUTTON PUSH USING AUTOBASE TECHNOLOGY

CABLE-FREE BASE OR ROVER OPERATION USING BLUETOOTH® TECHNOLOGY

INTEGRATED LICENSE-FREE 900 MHZ RADIO OR 450 MHZ UHF RADIO

SUPPORTS VRS OR TRIMBLE IBSS CORRECTIONS THROUGH THE TRIMBLE TSC3 OR TRIMBLE TABLET CONTROLLER

A FUTURE-PROOFED INVESTMENT WITH 220 CHANNELS AND THE ABILITY TO TRACK GPS, GLONASS AND GALILEO GIOVE A AND GIOVE B

TRIMBLE SPS882 GNSS SMART ANTENNA

The Trimble® SPS882 GNSS Smart Antenna offers unmatched flexibility for all your construction measurement needs. It is ideal for use on small and large job sites, as a pole-mounted rover system or as a temporary base station for other GNSS operations including machine control.

With Trimble SCS900 Site Controller Software, the SPS882 can help you:

- Determine cut/fill anywhere on the jobsite
- Stake out site or road features, utilities, daylight lines and side slopes
- Carry out site measurements for progress and material stockpile volume calculations
- Carry out as-built measurements, grade checks and laid material thickness checks

Using the advanced Trimble Maxwell™ 6 chip, the SPS882 GNSS Smart Antenna can "see" more GNSS constellations, satellites, and signals than traditional GPS, so you can expect greater accuracy in more challenging conditions such as under tree canopy and in urban areas. That also means more uptime using the system and more productivity for your job crews.

Fast to Set-up and Use

Rover set up is fast and easy—just switch on the receiver, start up the controller and you're ready to go. Because the receiver, antenna, radio, radio antenna and battery are integrated into one housing, you don't have to deal with cables and multiple components. And with Trimble AutoBase™ functionality you can also repeat daily set up of the SPS882 base station without the need for a controller. Simple to transport and fast to setup, the SPS882 GNSS Smart Antenna keeps your crews working, not wasting time with GNSS maintenance.

The fully upgradable SPS882 receiver can be configured in a variety of ways to suit any application, for example:

- As a portable base station only
- As a rover only with Precision or Location RTK accuracy
- As a flexible base or rover with Precision RTK accuracy

All options are available at the time of sale or as an upgrade.



TRIMBLE SPS882 GNSS SMART ANTENNA

GENERAL

Keyboard and display LED indicators for satellite tracking, radio link reception and power monitoring
 On/Off key for one-button startup
 Dimensions (W x D) 19 cm (7.5 in) x 11.2 cm (4.4 in)
 Weight 1.35 kg (2.97 lb) receiver only including radio and battery
 Complete system (rover including controller and pole)
 3.7 kg

ENVIRONMENTAL

Operating -40 °C to +65 °C (-40 °F to +149 °F)
 Storage -40 °C to +75 °C (-40 °F to +167 °F)
 Humidity 100%, condensing
 Waterproof IP67 for submersion to depth of 1 m (3.3 ft), dustproof
 Pole drop Designed to survive a 2 m (6.6 ft) pole drop onto concrete

MEASUREMENTS

- 220-channel L1C/A, L1/L2/L2C. Upgradable to L5 and GLONASS L1/L2C/A, L1/L2P Full Cycle Carrier
- Trimble EVEREST™ multipath signal rejection
- 4-channel SBAS L1 C/A, L5 (WAAS/EGNOS/MSAS)

CODE DIFFERENTIAL GPS POSITIONING²

Horizontal accuracy 0.25 m + 1 ppm RMS (0.8 ft + 1 ppm RMS)
 Vertical accuracy 0.50 m + 1 ppm RMS (1.6 ft + 1 ppm RMS)

REAL-TIME KINEMATIC (RTK) POSITIONING³

Horizontal accuracy 8 mm + 1 ppm RMS (0.026 ft + 1 ppm RMS)
 Vertical accuracy 15 mm + 1 ppm RMS (0.05 ft + 1 ppm RMS)

INITIALIZATION TIME

RTK operation with a single base station 1 second
 + 1 second per 10 km
 Regular RTK operation within RTK network Minimum 1.5 seconds
 + 0.5 seconds per 10 km
 Initialization reliability³ >99.9%

POWER

Internal Rechargeable, removable 7.4 V, 2.4 Ah
 Lithium-ion battery in internal battery compartment
 External External power input with over-voltage protection
 11 V DC to 28 V DC external power input
 Power consumption 3.2 W, in RTK mode with internal radio

OPERATION TIME ON INTERNAL BATTERY

Rover 5 hours; varies with temperature
 Base station with internal radio 3.7 hours; varies with temperature

REGULATORY APPROVALS

- FCC certification Class B Part 15, 22, 24
- Canadian ICES-003. Cet appareil numérique de la classe B est conforme à la norme NMB-003 du Canada
- Canadian RSS-310, RSS-210, and RSS-119
- Cet appareil est conforme à la norme CNR-310, CNR-210, et CNR-119 du Canada
- CE mark compliance
- C-tick mark compliance
- RoHS compliant
- WEEE compliant

COMMUNICATIONS

Lemo (Serial). 7-pin 05 Lemo, Serial 1, 3-wire RS-232
 Modem 1 (Serial) D-sub, Serial 2, Full 9-wire RS232
 Bluetooth wireless technology Fully-integrated, fully-sealed 2.4 GHz Bluetooth module⁴
 Integrated radios (optional) Fully-integrated, fully-sealed internal 450 MHz (UHF) Tx/Rx; Internal 900 MHz Tx/Rx
 Internal radio output. 0.5 W
 External GSM/GPRS, cell phone support. Supported via the SCS900 and SPS controller
 Receiver position update rate 1 Hz, 2 Hz, 5 Hz, 10 Hz, and 20 Hz positioning
 Correction data input/output CMR™, CMR+™, CMRx, RTCM3, RTCM 2.x (with Rover/Base upgrade)
 Data outputs NMEA, GSOFF

1 Receiver will operate normally to -40 °C. Internal batteries are rated to -20 °C.
 2 Accuracy and reliability may be subject to anomalies such as multipath, obstructions, satellite geometry, and atmospheric conditions. Always follow recommended practices.
 3 May be affected by atmospheric conditions, signal multipath, and satellite geometry. Initialization reliability is continuously monitored to ensure highest quality.
 4 Bluetooth type approvals are country specific.

Specifications subject to change without notice.

© 2009–2011, Trimble Navigation Limited. All rights reserved. Trimble and the Globe & Triangle logo are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. CMR, CMR+, EVEREST, Maxwell, Autobase and VRS are trademarks of Trimble Navigation Limited. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Navigation Limited is under license. All other trademarks are the property of their respective owners. PN 022482-2342-2 (08/11)



TRIMBLE AUTHORIZED DISTRIBUTION PARTNER

NORTH AMERICA

Trimble Heavy Civil Construction Division
 10355 Westmoor Drive, Suite #100
 Westminster, Colorado 80021
 USA
 800-361-1249 (Toll Free)
 +1-937-245-5154 Phone
 +1-720-587-4685 Fax
 www.trimble.com

EUROPE

Trimble Germany GmbH
 Am Prime Parc 11
 65479 Raunheim
 GERMANY
 +49-6142-2100-0 Phone
 +49-6142-2100-550 Fax

ASIA-PACIFIC

Trimble Navigation
 Singapore PTE Ltd.
 80 Marine Parade Road
 #22-06, Parkway Parade
 Singapore, 449269
 SINGAPORE
 +65 6348 2212 Phone
 +65 6348 2232 Fax



www.trimble.com